

## 1-needle, Long Arm (25"), Unison-Feed, Lockstitch Machine with Vertical-axis Large Hook


### 單針長臂綜合送料縫紉機

<b>CK-1508-25</b>	單針長臂	for heavy materials
<b>CK-1508NH-25</b>	自動供油	with automatic lubricating mechanism
<b>CK-1508NH-25-T</b>	粗線專用(#0)	for thick thread (#0)
<b>CK-1508NH-25-FL</b>	自動抬押腳	with pneumatic auto-lifter
<b>CK-1508NH-25-BT</b>	自動回縫及抬押腳	with automatic backtrack and auto-lifter



#### FEATURES:

- The machine is provided with 635mm (25") of working space. It is ideally suited to sewing processes require a larger space under the arm. Typical examples are the sewing of canvases and furniture.
- The maximum stitch length is 9mm, the needle bar stroke is 38mm, and an extra large steel hand-wheel with a diameter as large as 175mm, the machine supports the sewing of extra heavy materials.
- The machine is equipped as standard with a safety clutch for preventing hook breakage. Reset work can be done simply by pressing a button.



- 本機配有綜合送料機構與垂直軸大釜，以及可供縫製的工作範圍廣達653mm，適合於縫製大件以及厚料的物品，例如帳篷，汽車座椅及沙發等大型物品。
- 最大縫目可達9mm、押腳提升量可達16mm、與38mm的針棒衝程及大型手轉輪，適用於縫製極厚之物料。
- 採用兩倍大釜與梭仔，免除經常更換梭仔底線的麻煩，增進縫製效率。本機器並配置有安全裝置(離合器)，大釜卡線或有問題時，安全裝置會自動脫離以防止大釜與針之損壞。

#### SPECIFICATIONS:

Max. sewing speed 最高縫速	1,800 s.p.m.	Working space 工作範圍	635 mm
Max. stitch length 最大縫目	9 mm	Needle to be used 使用針	Organ DPx17 #23
Lift of the presser foot 押腳提升量	9 mm by Hand 16 mm by Knee	Needle system 針號	#20 ~ #25
Alternating vertical movement 押腳上下交互量	2.5 ~ 6.5 mm	Thread 線	#20 ~ #1
Needle bar stroke 針棒衝程	38 mm	Motor to be used 馬達	Clutch Motor, 1/2 HP, 4P