



CK-1508NH




1-needle, Unison-feed, Lockstitch Machine with Vertical-axis Large Hook (For Extra Heavy Materials)
單針綜合送料縫紉機（極厚物料之車縫）



This machine is equipped with unison feed mechanism and vertical-axis double-capacity hook. It is applicable to an extended range of heavy materials for industrial use, such as cargo handling belts and containers, as well as those for general use, such as car seats, sofas and bags, etc.

本機配有綜合送料機構與垂直軸大釜，適用於手提袋的手把、汽車座椅、沙發、箱包類等等之厚物料之縫製。



CHIKON

INDUSTRIAL SEWING MACHINE

FEATURES :

- * With the adoption of a new rectangular feed mechanism, an alternating vertical movement mechanism, and a unison-feed mechanism, the machine can feed heavy materials powerfully and smoothly. Well tensed seams are consistently produced without pitch errors.
- * The maximum stitch length is 9mm. The complete rectangular feed locus enables accurate feed of extra heavy materials while preventing stitch gathering.
- * The machine has adopted a dual-tension mechanism, with which the machine can support high-tension sewing with thick thread. This means that the machine produces seams of excellent quality on a broader range of materials, extending from light- to heavy-weight.
- * With its sufficient needle bar stroke of 38mm and long 190R needle, the machine supports the sewing of extra heavy materials.
- * The machine comes with an extra large steel hand-wheel with a diameter as large as 175mm.
- * The machine is equipped as standard with a safety clutch for preventing hook breakage. Reset work can be done simply by pressing a button.

- * 本機器採用綜合送料機構、新式正矩型送料與押腳上下交替量機構，能精準輕易的車縫厚重物料，縫目精確美觀。
- * 本機器配置雙張力機構，可對應粗線及高張力之縫製，可廣泛地對應於各種厚物料。
- * 最大縫目達9mm、押腳提升量達16mm、及38mm的針棒衝程與大型手轉輪，適用於縫製極厚之物料。
- * 採用兩倍垂直大釜與梭仔，免除經常更換梭仔底線的麻煩，並減少工時的浪費，增進縫製效率。
- * 大釜卡線或有問題時，安全裝置(離合器)會自動脫離，可防止大釜與針之損壞。



SPECIFICATIONS:

Max. sewing speed 最高縫速	2,000 s.p.m.	Needle to be used 使用針	Standard 190R or 135x17(Nm160)
Max. stitch length 最大縫目	9 mm	Needle system 針號	Nm125~ Nm200
Lift of the presser foot 押腳提升量	9 mm by Hand 16 mm by Knee	Thread 線	#20 ~ #1, B69~B207 Nm=40/3~8/3
Alternating vertical movement 押腳上下交互量	2.5~6.5 mm	Motor to be used 馬達	Clutch Motor, 3-phase, 1/2 HP, 4P
Needle bar stroke 針棒衝程	38 mm	N.W. / G.W. 淨重 / 毛重	45 / 48 KGS
Working space 工作範圍	255 mm	Meas. 材積	0.223 CBM

奇鋼精機廠有限公司
 Chikon Industrial Sewing Machine Co., Ltd.
 台北縣241三重市溪尾街108巷2號
 No. 2, Lane 108, Shi-Wei Street, San-Chung City,
 Taipei Hsien 241, Taiwan, R.O.C.
 Tel: +886-2-2286-8427 Fax: +886-2-2287-8708
 E-Mail: info@chikon.com.tw http://www.chikon.com.tw

