

CK-1541











1-needle, Unison-feed, Lockstitch Machine with Horizontal-axis Large Hook

單針綜合送料縫紉機

CK-1541 厚物料車縫

without safety mechanism

CK-1541-S 離合器裝置

with safety mechanism

CK-1541-FL 自動抬押腳

with pneumatic auto-lifter

CK-1541-BT 自動回縫及抬押腳

with automatic backtrack and

auto-lifter

FEATURES:

- · With its large needle bar stroke, higher presser foot lift, and newly adopted double-tension mechanism, the machine offers excellent sewing capabilities and responsiveness..
- The maximum stitch length is 9mm, the needle bar stoke is 36mm, and an extra large steel hand-wheel with a diameter as large as 175mm, the machine supports the sewing of extra heavy materials.
- · 本機器採用綜合送料機構、新式正矩型送料與押腳上下交替量機構,能精準輕易的車縫厚重物料,縫目精確美觀。 本機器配置張力機構,可對應粗線及高張力之縫製,可廣泛地對應於各種厚物料。
- ·最大縫目可達9mm、押腳提升量可達16mm、與36mm的針棒衝程及大型手轉輪,適用於縫製極厚之物料如手 提袋的手把、汽車座椅、沙發、箱包類等等。
- 採用兩倍水平大釜與梭仔,免除經常更換梭仔底線的麻煩,增進縫製效率。

















SPECIFICATIONS:

Max. sewing speed 最高縫速	2,500 s.p.m.	Working space 工作範圍	255 mm
Max. stitch length 最大縫目	9 mm	Needle to be used 使用針	Organ DPx17 #23
Lift of the presser foot 押腳提升量	9 mm by Hand 16 mm by Knee	Needle system 針號	#20 ~ #25
Alternating vertical movement 押腳上下提升量	2.5 ~ 6.5 mm	Thread 線	#30 ~ #5
Needle bar stroke 針棒衝程	36 mm	Motor to be used 馬達	Clutch Motor, 1/2 HP, 4P