



CK-471





Long Arm, Cylinder Bed, Upper & Lower Feed, Extra Heavy Duty, Lockstitch Sewing Machine

長臂筒型單針上下送料縫紉機（極厚物料之車縫）



This machine is equipped with semi-rotary large capacity shuttle hook, suitable for sewing heavy weight materials. Used for harness, tack, saddlery, canvas, sport equipment, footwear. Such products as: safety belts, golf bags, luggage, tarpaulins, tents, book bindings, orthopedic appliances, boots, holsters, knife sheath, purses, etc.

本機配有半迴轉式旋梭（大月眉），適用於手提袋的手把、棒球手套、安全帶、帳篷、椅墊、鞋類、箱包類等等之極厚物料筒狀物品之縫製。



CHIKON

INDUSTRIAL SEWING MACHINE

FEATURES :

- * With upper & lower feed, the machine can sew accurately and easily several sheets of heavy weight materials piled up together.
- * The upper feed amount can be increased or decreased by 30% with respect to the lower feed amount.
- * The lifting amount of presser foot is as high as 20mm, suitable for stitching the extra heavy-weight materials.
- * The machine is provided with a free space measuring 420mm wide. It allows the operator to handle a large sewing product with ease.
- * Applied the semi-rotary large shuttle hook & bobbin, could reduce the frequency of changing the bobbin thread and increase the sewing efficiency.
- * The machine incorporates a built in bobbin winder, which can be reached with ease during sewing.

- * 上下送之送料方式，送料力量強大，能精準與輕易的車縫多層之厚重物料，縫目精確美觀。
- * 上送料量相對於下送料量可增加或減少30%。
- * 押腳提升量達20mm，適用於縫製極厚之物料。
- * 可供縫製的工作範圍廣達420mm，適合於縫製大的物品。
- * 採用半迴轉式的大月眉與大梭仔，可以減少更換底線之次數，增加縫製效率。
- * 安裝於機頭上之梭仔捲線裝置，操作簡便。



SPECIFICATIONS:

| | | | |
|-----------------------------------|---------------------------------|--------------------------|---------------------------------------|
| Max. sewing speed 最高縫速 | 800 s.p.m. | Needle to be used 使用針 | Schmetz 794 Nm230 (Organ DYx3 #26) |
| Max. stitch length 最大縫目 | 11 mm | Needle system 針號 | Nm130 ~ Nm280 (#21 ~ #28) |
| Lift of the presser foot 押腳提升量 | 12 mm by Hand 20 mm by Pedal | Thread 線 | #00 ~ #8 |
| Diameter of cylinder-bed 筒徑 | 81 mm | Motor to be used 馬達 | Clutch Motor, 3-phase, 3/4 HP, 4P |
| Needle bar stroke 針棒衝程 | 56 mm | N.W. / G.W. 淨重 / 毛重 | 53 / 62 KGS |
| Working space 工作範圍 | 420 mm | Meas. 材積 | 0.223 CBM |

奇鋼精機廠有限公司
 Chikon Industrial Sewing Machine Co., Ltd.
 台北縣241三重市溪尾街108巷2號
 No. 2, Lane 108, Shi-Wei Street, San-Chung City,
 Taipei Hsien 241, Taiwan, R.O.C.
 Tel: +886-2-2286-8427 Fax: +886-2-2287-8708
 E-Mail: info@chikon.com.tw http://www.chikon.com.tw

